

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

1. REPORT DATE (DD-MM-YYYY)

2. REPORT TYPE

Technical Papers

3. DATES COVERED (From - To)

4. TITLE AND SUBTITLE

5a. CONTRACT NUMBER

5b. GRANT NUMBER

5c. PROGRAM ELEMENT NUMBER

6. AUTHOR(S)

5d. PROJECT NUMBER

5e. TASK NUMBER

5f. WORK UNIT NUMBER

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

Air Force Research Laboratory (AFMC)
AFRL/PRS
5 Pollux Drive
Edwards AFB CA 93524-7048

8. PERFORMING ORGANIZATION
REPORT

9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)

Air Force Research Laboratory (AFMC)
AFRL/PRS
5 Pollux Drive
Edwards AFB CA 93524-7048

10. SPONSOR/MONITOR'S
ACRONYM(S)

11. SPONSOR/MONITOR'S
NUMBER(S)

12. DISTRIBUTION / AVAILABILITY STATEMENT

Approved for public release; distribution unlimited.

13. SUPPLEMENTARY NOTES

14. ABSTRACT

20021030 068

15. SUBJECT TERMS

16. SECURITY CLASSIFICATION OF:

17. LIMITATION
OF ABSTRACT

18. NUMBER
OF PAGES

19a. NAME OF RESPONSIBLE
PERSON

Leilani Richardson

19b. TELEPHONE NUMBER
(include area code)
(661) 275-5015

a. REPORT

b. ABSTRACT

c. THIS PAGE

Unclassified

Unclassified

Unclassified

A

Standard Form 298 (Rev. 8-98)
Prescribed by ANSI Std. Z39.18

2 separate items enclosed

ON TIME = KUDOS !!!

MEMORANDUM FOR PRS (In-House Publication)

FILE

FROM: PROI (STINFO)

27 Sept 2002

SUBJECT: Authorization for Release of Technical Information, Control Number: **AFRL-PR-ED-AB-2002-229**
55595 = Archambault, Mark, "Computation of Multimodal Size-Velocity-Temperature Spray Distribution Functions"

9th International Conference on Liquid Atomization and Spray Systems 2003 (Statement A)
(Sorrento, Italy, 13-18 July 03) (Deadline: 31 Oct 02)

Computation of Multimodal Size-Velocity-Temperature Spray Distribution Functions

Mark R. Archambault

*Air Force Research Laboratory
Propulsion Directorate
Space and Missile Propulsion Directorate
Edwards AFB, CA 93524*

Understanding and modeling spray flows is of primary interest in a wide variety of applications including those associated with liquid fuel injectors, industrial coating processes, and agricultural sprays. Probably the most common approach to computing spray flows is the Lagrangian-Eulerian, or particle-tracking method¹. This method provides an indirect means of solving for the statistical quantities which characterize a spray, by tracking individual particles (or parcels), counting them in specified volumes, and then forming the statistics of interest. Solution of the governing equations does not provide the droplet statistics directly—they result from post-computation averaging of droplet data. While this approach has provided excellent results in many applications, it has some potentially significant drawbacks. Foremost among these is the need to integrate (or simulate) until the statistics of interest are converged. This can lead to prohibitively long computational times.

An alternative approach—one which does not involve simulation or stochastic integration—is to directly compute the evolution of the probability density function (PDF) describing the drops. The purpose of this paper is to continue exploring an alternative method of solving the spray flow problem. The approach is to derive and solve a set of Eulerian moment transport equations for the quantities of interest in the spray, coupled with the appropriate gas-phase (Eulerian) equations. A second purpose is to continue to explore how a maximum-entropy criterion may be used to provide closure for such a moment-based model. The hope is to further develop an Eulerian-Eulerian model that will permit one to solve for detailed droplet statistics directly without the use of stochastic integration or post-averaging of simulations.

This alternative approach, the Maximum Entropy Moment Closure (MEMC) approach, has previously been presented,^{2,3} showing that the method is capable of propagating a joint diameter-velocity PDF. This is done by discretizing the diameter axis and deriving sets of velocity moment and expected number density transport equations—one set for each diameter bin. Upon solving these and the gas phase equations, one can reconstruct the joint diameter-velocity PDF which can be integrated to obtain any statistic of interest. Results have shown^{2,5} a clear wave-like behavior associated with the spray and have revealed structure within the spray

DISTRIBUTION STATEMENT A
Approved for Public Release
Distribution Unlimited

such as a larger mean diameter at the spray's leading edge due to the effects of drag in the case where the mean injection velocity was greater than the mean gas velocity. These results compare well with the results from a conventional Lagrangian simulation approach.

In the present work, the details of including the random variable of temperature into the phase space and incorporating the effects of energy exchange with the gas phase will be presented. This is an important first step in extending the model for use with non-isothermal sprays. The challenges to be discussed will be how to model the mixed temperature-velocity moments and the energy exchange terms. In addition, the model will be extended to predict multi-modal distribution functions. This is done by solving additional sets of equations representing each mode of the PDF and recombining them into a single PDF. This will ultimately lead to the ability to predict spray distributions in regions of recirculation or intersecting sprays where there may be significant differences in the droplet characteristics. These extensions will be tested on a quasi-one-dimensional model problem and results of expected number density, mean and mean-squared velocity, and mean, mean-squared, and mean-cubed temperature as a function of position and time will be presented for both single- and multi-modal distributions.

References

1. Dukowicz, J. K., "A Particle-Fluid Numerical Model for Liquid Sprays," *J. Comp. Phys.*, vol. 35, pp. 229-253, 1980.
2. Archambault, M. R., "A Maximum Entropy Moment Closure Approach to Modeling the Evolution of Spray Flows," Ph.D. thesis, Stanford University, Stanford, CA, 1999.
3. Archambault, M. R., Edwards C. F., & MacCormack, R. W., "Computation of Spray Dynamics by Moment Transport Equations I: Theory and Development," accepted for publication in *Atomization and Sprays*, 2002.
4. Archambault, M. R., Edwards, C. F., & MacCormack, R. W., "Computation of Spray Dynamics by Moment Transport Equations II: Application to Calculation of a Quasi-One-Dimensional Spray," accepted for publication in *Atomization and Sprays*, 2002.